Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

DELTA

GE SERIES HIGH PERFORMANCE IEC CONNECTOR FILTERS

INTRODUCTIONS

1. A high performance general purpose filter with an IEC connector providing effective EMI suppression.
2. Bleeder resistor can be added for "G3E", "W3E", "G3S" & "G3C" types with suffix "-R" on part numbers.
3. Safety Approval: EG3H, EW3V: UL, CSA, VDE & SEV
   EG3V & EG3Q: UL, CSA & VDE
   HG3J: UL, CSA, VDE & SEMKO
   20GE: UL, CSA & VDE
4. With optional Y-Cap 3300pF.

COMPONENTS

PART NO.	Cx (uF)	L (mH)	Cy (pF)	R (Ω)
01GEEG3E/W3E/-R	0.1	6.5	2200	1M
01GEEG3H/G3V/W3V		3	3300	–
01GEEG3S/-R		10.5	2200	1M
03GEEG3E/W3E/W3ES/-R		2.5		
•03GEEW3ES/-R				
03GEEG3H/G3V/W3V			3300	–
03GEEG3S/-R			2200	1M
•03GEEG3Q/W3Q-R		4		
03GEEW3J		2.4		–
03GEHG3J				
06GEEG3E/W3E/W3ES/-R		0.8		1M
06GEEG3H/G3V/W3V			3300	–
06GEEG3S/-R		1.05	2200	1M
••06GEEG3Q/W3Q-R		1.5		
•••10GEEG3C/W3C/-R		0.4		
10GEEG3E/W3E/W3ES/-R		0.2		
10GEEG3S/-R				
*10GEEG3Q/W3Q/-R		0.3		
**15GEEG3E/W3E/-R		0.2		
***20GEEG3E/W3E/-R		0.3		

• UL, CSA approved to 4A 115/250V
•• UL, CSA approved to 8A 115/250V
••• VDE approved to 8A/250V
* UL, CSA approved to 13A 115/250V
** VDE approved to 10A/250V
*** VDE approved to 16A/250V

INSERTION LOSS (TYPICAL)

03GEEG3E ------ COMMON MODE -------- DIFF. MODE
06GEEG3E - - - - COMMON MODE ——— DIFF. MODE



20GEEG3E ····· COMMON MODE ····· DIFF. MODE



SPECIFICATIONS

1. Maximum leakage current each
   line-to-ground @ 115VAC 60Hz: 0.25mA
   @ 250VAC 50Hz: 0.45mA
2. Hipot rating (one minute)
   line-to-ground: 2250VDC
   line-to-line: 1450VDC
3. Operating frequency: 50/60Hz
4. Rated voltage: 115/250VAC

ELECTRICAL SCHEMATIC



MINIMUM INSERTION LOSS IN dB

COMMON MODE (L-G) IN 50 OHM SYSTEM						
CURRENT	FREQUENCY-MHz					
RATING	.15	.50	1.0	5.0	10	30
1A(E)(S)	28	35	38	38	40	40
1A(H)	26	36	44	54	55	55
1A(G3V)	20	30	35	40	40	40
1A(W3V)	24	35	42	50	55	55
3A(E)(S)(Q)	20	25	30	38	40	40
3A(H)	24	30	38	50	55	55
3A(G3J,W3J)	20	25	30	38	40	40
3A(G3V)(W3V)	20	29	36	48	46	50
6A(E)(S)	12	18	24	35	40	40
6A(H)	15	25	32	45	50	50
6A(Q)	15	20	20	35	40	55
6A(G3V)(W3V)	14	23	30	42	35	40
10A(E)(S)	4	10	13	28	35	40
10A(C)	10	15	15	25	30	35
10A(Q)	10	12	15	30	32	45
15A(E)	4	10	13	28	35	40
20A	8	10	15	25	30	35



ASSEMBLY FROM FRONT

MECHANICAL CONSTRUCTION

EG3E, EG3Q (Optional soldering lug or wire type)



EG3S



EG3H



EG3V



EW3V



ALL WIRE LEADS 4.0" LONG MIN.

UNIT: INCH / mm



ASSEMBLY FROM FRONT

MECHANICAL CONSTRUCTION

EW3J



EW3ES



HG3J



20GEEG3E (Optional wire type)



ALL WIRE LEADS 4.0" LONG MIN.

SUGGESTED MOUNTING CUTOUT
(MOUNTING FROM REVERSE)

UNIT: INCH / mm